CeraSolv 237
Thinner for Cover Coat

Chemical basis:
Solvent mixture

Characteristics:
Appearance: clear liquid
Solubility: partially miscible with water
Density (20 °C): approx. 0,91 g/cm³

Safety data: see MSDS

Shelf-life / Packaging:
12 months when stored in dry and cool conditions
drums of 25 and 180 kg

Application:
For some applications ceramic cover coat dries too fast or its viscosity must be reduced. **CeraSolv 237** lowers the viscosity very effectively, prevents the cover coat from drying and provides an even better smoothness of the printed surface.
CeraSolv 237 should be added from 1% up to max. 5% in weight of the cover coat quantity.

Safety information:
On account of its solvent content **CeraSolv 237** must be kept away from all open flames. Containers should be stored tightly sealed. It must not get into the hands of children. Only use in well ventilated areas. Avoid contact with the eyes and the skin. Do not eat, drink or smoke while working. Do not allow to enter the waste water system. See MSDS for further information. **CeraSolv 237** is a solvent mixture and prolonged contact with the skin can lead to loss of natural oils. Hence, skin care with a good hand cream is recommended after work.

Note: Opened drums should always be re-fastened carefully.

The above results have been obtained from trials in our laboratory and plant. In the light of changing conditions they can serve only as a guide and are therefore offered without obligation. We ask you to observe the possible rights of third parties.

January 30 2021